

LIST OF TARIFF SUSPENSIONS **BELOW** THE THRESHOLD FOR AUTOMATIC PROLONGATION

For the 1 January 2013 round of suspension prolongations, the Commission has adapted the methodology used in previous exercises so that it reflects the new threshold set by the Communication from the Commission adopted in 2011. Instead of the amount used in previous rounds justifying an automatic prolongation (1 000 000 EUR of import value), the list below only contains suspension measures which have collected less than 750 000 EUR in the last 12 months.

The full list of suspensions which expire on 31 December 2012 has already been distributed to you on CIRCA. However, following the established practice, you should submit prolongation requests **only** for the codes below. The codes in ~~strikethrough~~ already fulfil the duty loss condition, for them no further application is necessary.

The suspension with code 2008 93 91 20 is an isolated case and will be discussed separately.

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2008 60 19 ex 2008 60 39	30 30	Sweet cherries containing added spirit, whether or not with a sugar content of 9 % by weight, of a diameter of not more than 19,9 mm, with stone, for use in chocolate products(1)	10 %(3)	31.12.2012
ex 2850 00 20	30	Titanium nitride with a particle size of not more than 250 nm, (CAS RN 25583-20-4)	0 %	31.12.2012
ex 2904 10 00	40	Sodium toluene-4-sulphonate (CAS RN 657-84-1)	0 %	31.12.2012
ex 2914 19 90	30	3-Methylbutanone (CAS RN 563-80-4)	0 %	31.12.2012
ex 2914 19 90	40	Pentan-2-one (CAS RN 108-10-1)	0 %	31.12.2012
ex 2914 39 00	20	Stearoyl benzoyl methane (CAS RN 58446-52-9)	0 %	31.12.2012
ex 2914 50 00	70	16 α ,17 α -Epoxy-3 β -hydroxypregn-5-en-20-one, (CAS RN 974-23-2)	0 %	31.12.2012
ex 2930 90 99	67	3-Bromomethyl-2-chloro-4-(methylsulphonyl)-benzoic acid	0 %	31.12.2012

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2930 90 99	69	2-Amino-4-methylsulphonyl- <i>N</i> -methylaniline (CAS RN 73097-51-5)	0 %	31.12.2012
ex 2930 90 99	71	Triphenylsulphonium chloride (CAS RN 4270-70-6)	0 %	31.12.2012
ex 2930 90 99	82	Sodium toluene-4-sulphinat (CAS RN 824-79-3)	0 %	31.12.2012
ex 2930 90 99	83	Methyl- <i>p</i> -tolyl sulphone (CAS RN 3185-99-7)	0 %	31.12.2012
ex 2933 79 00	30	5-Vinyl-2-pyrrolidone (CAS RN 7529-16-0)	0 %	31.12.2012
ex 2934 99 90	74	2-Isopropylthioxanthone (CAS RN 5495-84-1)	0 %	31.12.2012
ex 2934 99 90	78	1,2,4-Thiadiazole-3-acetic acid 5-[(ethoxycarbonyl)amino]- methyl ester (CAS RN 150215-07-9)	0 %	31.12.2012
ex 3204 15 00	10	Dye C.I. Vat Orange 7 (C.I. Pigment Orange 43)	0 %	31.12.2012
ex 3204 17 00	30	Dye C.I. Pigment Yellow 97	0 %	31.12.2012
ex 3208 90 91	10	Preparation on the basis of polyhydroxyamide containing at least naphthoquinone ester derivate or tosylate dissolved in γ -butyrolactone and/or 2-methoxy-1-methylethyl acetate	0 %	31.12.2012
ex 3808 93 27	20	Organic solution of Clethodim (ISO), with a Clethodim content of 37 % (\pm 2 %) or 70 % (\pm 2 %) by weight	0 %	31.12.2012
ex 3815 90 90	85	Catalyst based on aluminosilicate (zeolite), for the alkylation of aromatic hydrocarbons, for the transalkylation of alkylaromatic hydrocarbons or for the oligomerization of olefins(1)	0 %	31.12.2012
ex 3824 90 97	47	4-Methoxysalicylaldehyde, dissolved in <i>N</i> -methyl pyrrolidone	0 %	31.12.2012
ex 3824 90 97	70	Paste containing by weight 75 % or more, but not more than 85 % of copper, and also containing inorganic oxides, ethyl cellulose and a solvent	0 %	31.12.2012
ex 3919 10 80	55	Acrylic foam tape, covered on one side with a	0 %	31.12.2012

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3919 90 00	53	heat activatable adhesive or an acrylic pressure sensitive adhesive and on the other side with an acrylic pressure sensitive adhesive and a release sheet, of a peel adhesion at an angle of 90 ° of more than 25 N/cm (as determined by the ASTM D 3330 method)		
ex 3919 90 00 ex 9001 20 00	47 40	Polarizer film, in rolls, consisting of a multilayered polyvinyl alcohol film, supported on either side by a triacetyl cellulose film, with a pressure sensitive adhesive and release film on one side	0 %	31.12.2012
ex 3919 90 00	55	Rolls of biaxially oriented polypropylene film with: — a self adhesive coating, — a width of 363 mm or more, but not more than 507 mm, — a total film thickness of 10 µm or more but not more than 100 µm, for use in the protection of LCD displays during the manufacturing of LCD modules(1)	0 %	31.12.2012
ex 3920 79 90	10	Cellulose acetyl butyrate film, whether or not combined with a polycarbonate layer, of a thickness of not more than 0,81 mm containing a micro-louvre with a typical viewing angle of 30 degrees measured on each side of the surface normal	0 %	31.12.2012
ex 3920 92 00	30	Polyamide film of a thickness of not more than 20 µm, coated on both sides with a gas barrier layer which consists of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 µm	0 %	31.12.2012
ex 7005 10 25	10	Float glass: — of a thickness of 2,0 mm or more but not more than 2,4 mm, — coated on one surface with a fluorine doped tin dioxide reflective layer	0 %	31.12.2012
ex 7006 00 90 ex 8529 90 92	60 46	Soda-lime glass plates with: — a strain point of more than 570 °C — a thickness of 1,7 mm or more but not more than 2,9 mm	0 %	31.12.2012

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul style="list-style-type: none"> — dimensions of 1144 mm (±0,5 mm) × 670 mm (±0,5 mm) or 1164 mm (±0,5 mm) × 649 mm (±0,5 mm) and — whether or not containing: <ul style="list-style-type: none"> — an indium-tin oxide film, or — a grid of electrodes made from silver paste covered by dielectric material 		
ex 7007 19 20	20	Tempered or semi-tempered glass plate of a diagonal size of 81 cm or more, but not more than 186 cm, with one or more polymer layers, whether or not painted or with coloured or black ceramics around the surrounding edges, for use in the manufacture of goods falling within heading 8528(1)	0 %	31.12.2012
ex 8108 90 30	20	Bars, rods and wire of alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, for use in the manufacture of silencers and exhaust pipes of subheadings 8708 92 or 8714 10 00(1)	0 %	31.12.2012
ex 8108 90 50	40	Titanium-alloy sheets for the manufacture of structural parts of aircrafts(1)	0 %	31.12.2012
ex 8108 90 50	50	Plates, sheets, strips and foils of an alloy of titanium, copper and niobium, containing by weight 0,8 % or more but not more than 1,2 % of copper and 0,4 % or more but not more than 0,6 % of niobium	0 %	31.12.2012
ex 8407 31 00	10	Two stroke internal combustion engines, of a cylinder capacity of not more than 30 cm ³ for use in the manufacture of portable motorised scooters falling within subheading 8711 10 00(1)	0 %	31.12.2012
ex 8419 89 98	30	Apparatus for vapour deposition of parylene for use in the manufacture of drug eluting stents(1)	0 %	31.12.2012
ex 8419 89 98	40	Solution preparation apparatus for the treatment of materials by a process involving a change of temperature for use in the manufacture of drug-eluting stents(1)	0 %	31.12.2012

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8462 21 80	10	Numerically controlled stent crimping machine comprising a base, a pneumatic crimp head and a motorised product positioning mechanism (V-block) to crimp a stent onto the balloon of a catheter using radial pressure in the manufacture of drug eluting stents(1)	0 %	31.12.2012
ex 8477 59 80	10	Machinery for working rubber or plastic for use in the manufacture of drug-eluting stents(1)	0 %	31.12.2012
ex 8529 90 65	80	Scan driver boards for generating electric pulses for scanning to certain electrodes in a glass panel, comprising at least semiconductor chips	0 %	31.12.2012
ex 9032 10 89	20	Thermostat, damper or bimetal with, — an opening temperature of +7 °C (± 1,5 °C), closing temperature of -4 °C (± 1,5 °C)for damper thermostat, — an opening temperature of +8 °C (± 3 °C) for bimetal thermostat; for use in the manufacture of frost free refrigerators(1)	0 %	31.12.2012